6155 MH



As a high value crop producer you need machines that perfectly adapt to the environment they need to work in, incl. an exceptionally high ground clearance, a creeper option and full precision ag functionality. Welcome to the 6155MH.



NOTHING RUNS LIKE A DEERE



680 MM **GROUND CLEARANCE**

With a ground clearance of 680mm¹ the 6155MH offers you all the freedom you need to maintain your high-value crops.

Standard Tire Size: 320/90R50











WHY COMPROMISE?

High-value crops call for specialised equipment with very specific productivity characteristics. That is why we build the 6155MH and designed it to outperform in the applications that are important to you.

1 | ALL THE POWER YOU NEED

Get all the power you need with less fuel and low emissions from our 6.8 | 6 cyl. engine with 172 hp (126 kW) max. power and extended drain intervals of up to 750 hours.

2 | CHOICE OF TRANSMISSIONS

Choose between our renowned 16/16 PowerQuad™ Plus, 20/20 AutoQuad™ Plus and 20/20 CommandQuad™ Plus transmissions with maximum transport speeds of 30 km/h. For tasks that require you to go extra slow and steady, a creeper option lets you work at speeds as low as 72 m/h.

3 | HITCHES AND HYDRAULICS

Conveniently located between the rear hitch rails, the SCV stack groups together 4 SCV's. A pressure and flow compensated (PFC) system produces a hydraulic flow of 114 l/min.



4 | PRECISION FROM THE START

The StarFire[™] 7000 Receiver enables you to receive an SF-RTK signal to benefit from AutoTrac™ quidance with ultimate +/- 2.5 cm pass-to-pass accuracy. Connect to the John Deere Operations Center, and you can carefully plan your jobs during off-season and distribute them to all your machinery2.

SPECIFICATIONS

6MH MODELS	MAX. POWER (ECE-R120), HP (KW)	ENGINE TYPE	TRANSMISSION OPTIONS	CREEPER
6155MH	172 (126)	PowerTech PVS Engine 6.8L, 6 cylinder with Common Rail	16/16 PowerQuad™ Plus, 30 km/h	
			20/20 AutoQuad™ Plus, 30 km/h	
			20/20 CommandQuad™ Plus, 30 km/h	-

□ optional

not available